



Cola® Carb BEA

Low Foaming Wetting Agent

INCI NAME Sodium Butoxyethoxy Acetate
CAS NUMBER 67990-17-4, 111-76-2
LISTINGS USA (TSCA); EU (EINECS); Canada (DSL); Japan (ENCS); New Zealand (NZIoC); Korea (ECL); New Zealand (NZIoC); China (IECSC)

Cola® Carb BEA is an extremely low foaming wetting agent, stable to high acid and alkali. It is soluble in 20% HCl and 20% KOH.

APPLICATIONS

- Metal cleaning
- Bottle washing
- Steam cleaning
- Wax stripping
- Cleaning of food plants and handling areas



SPECIFICATIONS

Appearance @ 25°C	Clear Liquid
% Active (Calculated)	46.0 Min.
% Moisture (K.F.)	47.0 - 51.0
pH, as is	6.0 – 8.0
% Sodium Chloride	3.0 Max.



PERFORMANCE TESTING

Solubility 5% Active

20% HCl	Clear
25% H ₂ SO ₄	Insoluble
20% KOH	Clear
25% NaOH	Cloudy

1% Active Hamilton Beach Foam Test

Immediate	90
15 sec.	85
30 sec.	75
1 min.	65

STORAGE AND HANDLING

Cola® Carb BEA should be stored in closed containers. Shelf life is 24 months from date of manufacture. Cola® Carb BEA is shipped in poly 55-gal drums, net weight 450 lbs (204.1 kg). A Safety Data Sheet is available at www.colonialchem.com.

Colonial Chemical

225 Colonial Drive • South Pittsburg, TN 37380
Phone: 423-837-8800 • Fax: 423-837-3888

www.colonialchem.com

Innovative Specialty Surfactants