

# Cola®Cor 200

### Metalworking Corrosion Inhibitor

CHEMICAL NAME

Carboxylate

US (TSCA); Canada (DSL); New Zealand (NZIoC); China (IECSC); Korea (ECL)

**Cola®Cor 200** is a water-soluble carboxylate that is useful in a variety of metalworking, detergent, aerosol, and water-based coating applications. Aqueous solutions are low foaming, providing effective corrosion protection and surface activity in use treat levels (3%). For optimum rust protection, solution pH should be adjusted to 8.5 or greater with amine of choice. Cola®Cor 200 exhibits excellent tolerance to hard water and aqueous films dry to tack free surfaces. Does not contain boron, phosphates, chromates, nitrites or metallic cations.

#### **BENEFITS**

- Excellent tolerance to hard water
- · Aqueous films dry to tack free surface

#### **SPECIFICATIONS**

Appearance	Clear Liquid
pH (1% solution)	6.0 – 8.0
Activity, %	95 Min.

#### STORAGE AND HANDLING

Cola<sup>®</sup>Cor 200 is shipped in 55 gal. drums, net weight 450 lbs (204.1 kg) or 275 gal. totes. Cola<sup>®</sup>Cor 200 should be stored in closed containers. Shelf life is 12 months from date of manufacture. A Safety Data Sheet is available at www.colonialchem.com.

## Colonial Chemical, Inc.

225 Colonial Drive · South Pittsburg, TN 37380 Phone: 423-837-8800 · Fax: 423-837-3888 www.colonialchem.com