



Cola®Dry N3

Non-MSO Spray Wax Concentrate

REGISTRATIONS TSCA (US), NDSL (Canada), IECSC (China)

Cola®Dry N3 is a 100% active, non-mineral seal oil based drying agent for professional car washes. Cola®Dry N3 can be used in areas where hydrocarbon effluent restrictions are stringent and allow operators to stay within the capacity of current effluent treatment systems.

BENEFITS

- Hydrocarbon-free
- Efficient, time saving
- Optimized for drying with minimal spotting

APPLICATIONS

- Vehicle drying
- Wipe and shine

DILUTION GUIDELINES

For direct injection, this product can be used at 1500–2000: 1 dilution. Cola®Dry N3 can also be diluted to different concentrations without risk of thickening or gelling. As an example, one gallon of Cola®Dry N3 can be diluted into five gallons of water to make an economical, efficient drying agent.

DILUTION GUIDELINES

	Premium	Regular	Economy
Cola®Dry N3	40	30	25
Soft Water	60	70	75
Max. Dilution @ Use	800:1	500:1	300:1

SPECIFICATIONS

Appearance	Clear Liquid
Active, %	~100
pH (10% aqueous)	5.0 – 7.0
Flash Point, °C	> 95 (Non-Flammable)
Specific Gravity	0.966



FORMULATION

Wash and Shine

INGREDIENT	%
1 Cola®Dry N3	5.0
2 Cola®Teric SC	5.0
3 Water	90.0

Dilution at use: 10-30:1

Wipe and Shine

INGREDIENT	%
1 Cola®Dry N3	25.0
2 Soft Water	75.0

Dilution at use: 10-50:1

STORAGE AND HANDLING

Cola®Dry N3 is shipped in 55 gal. poly drums, net weight 420 lbs (190.5 kg) or totes (2100 lbs. [952.5 kg]). Cola®Dry N3 should be stored in closed containers. Shelf life is 12 months from date of manufacture. A Safety Data Sheet is available at www.colonialchem.com.

Colonial Chemical, Inc.

225 Colonial Drive · South Pittsburg, TN 37380
Phone: 423-837-8800 · Fax: 423-837-3888

www.colonialchem.com

Innovative Specialty Surfactants