

Cola®Teric JEM

Low Foaming Surfactant

DESCRIPTION Mixed C8 Amphocarboxylates

LISTINGS US (TSCA); Japan (ENCS); Philippines (PICCS); Korea (ECL)

Cola®Teric JEM, derived from mixed caprylic and ethylhexoic acids, is a surfactant with low foaming characteristics that is stable in alkaline medium. Cola®Teric JEM can be sprayed onto dry caustic soda, which will not discolor even after prolonged storage. Cola®Teric JEM

is recommended for use in bottle washing compounds, wax stripping formulations, for alkaline degreasing (containing 12 to 18% caustic soda), electrolytic degreasing, and fruit and vegetable lye peeling.



PERFORMANCE

Cola®Teric JEM reduces the surface tension of water and 4% caustic soda solutions, as the following typical results demonstrate:

Cola®Teric JEM, %	Dynes/cm in 4% NaOH	Dynes/cm in H ₂ O
1.0	29.0	28.7
0.5	29.1	29.3
0.25	29.8	29.8
0.12	32.3	30.5
0.06	35.1	30.9

Wetting and penetrating properties of Cola®Teric JEM were tested by the Draves-Clarkson Test in 20% caustic solution at 20°C. A sinking time of 41 seconds was obtained with only 0.175% Cola®Teric JEM. Wetting times were shorter at higher temperatures.

© 2014, Colonial Chemical, Inc. All rights reserved. 8/14

TYPICAL PROPERTIES

	Cola®Teric JEM	
Appearance	Clear Liquid	
pH, (as is @ 25°C)	10.0 – 10.5	
Solids, %	33.0 – 36.0	
Sodium Chloride, %	5.0 – 6.0	
Color, Gardner '98	5 Max.	

STARTING FORMULATIONS

Bottle Washing Concentrate

	INGREDIENT	%
1	Water	qs 100.00
2	Sodium Gluconate	20.00
3	Cola®Teric JEM	1.50
4	EDTA	5.00
5	Nonoxynol-15	0.50

This concentrate is to be metered into the caustic bottle washing solution. A suggested ratio is one part concentrate to one hundred parts of 6% sodium hydroxide solution. However, this ratio may be varied depending on individual requirements.

Low Foaming Wax Stripper

	I	NGREDIENT	%
1	١	Water	qs 100.00
2) (Sodium Metasilicate Pentahydrate	5.00
3	} -	Tetrapotassium Pyrophosphate	4.80
	1 (Cola®Teric JEM	4.00
5)	Trisodium Phosphate	3.00
6	5 E	Butoxyethanol	1.00

Certified to Contain Less than 10 ppm Heavy Metals/Iron.

Colonial Chemical, Inc.

225 Colonial Drive · South Pittsburg, TN 37380 Phone: 423-837-8800 · Fax: 423-837-3888

www.colonialchem.com

Natural Surfactants



